CHPV - S20시리즈 1500VDC - DC Contactor - 상품코드 : 086000048



*1500VDC
*20A High Voltage Direct Current Relay
*1 Form A contact arrangement
*Designed to meet cUL,CE requirements

제품 상세 정보 (Product Features)

Part Name: CHPV - S20
Contact Arrangement:1 Form A
Contact Load: 20A High Voltage
Coil Power: 2.6W

"추가제품옵션"을 통해서 "샘플&견적요청"가능합니다.

※ 유의사항

상기 제품에 첨부된 데이터시트는 참고용입니다.
자세한 데이터시트를 원하실 때에는 당사에 문의 바랍니다.

기술데이터

Drawing

CONTACT DATA

Main Contact Arrangement	1 Form A
Initial Contact Voltage Drop	≤90 mV at 20 A
Rated Current (resistive load)	20A
Rated Switching Voltage	1500VDC
Max. Switching Power (1500VDC)	30kW
Max. Breaking Current	200A (1000VDC)
Min.Applicable Load	6VDC, 1A

Contact Data

TEL: 02 - 716 - 6737~8 FAX: 02 - 701 - 8424 E - mail: webmaster@dongyangele.co.kr www.dongyangele.co.kr

Specifications are subject to change without notice. Specifications in this catalog are just for reference. The detail specification and drawing sheets will be provided upon request. Copyright. 2013 DONGYANG Electronic Inc. All rights reserved

CHARACTERISTICS


Operate Time(at nominal voltage)		≤15ms
Release Time(at nominal voltage)		≤5ms
Insulation Resistance		> 1000 MΩ (at 1000 VDC)
Dielectric Strength	Between Coil and Contacts	4,000 VAC, 50/60 Hz (1min)
	Between Open Contacts	3,000 VAC, 50/60 Hz (1min)
Vibration		10Hz ~ 500Hz, 49 m/s^2
Shock Resistance	Functional	196 m/s^2
	Destructive	490 m/s^2
Ambient temperature		-40℃ ~ 85℃
Humidity		5%RH to 85%RH
Weight		140g


Characteristics

TEL: 02 - 716 - 6737~8 FAX: 02 - 701 - 8424 E - mail: webmaster@dongyangele.co.kr www.dongyangele.co.kr

Specifications are subject to change without notice. Specifications in this catalog are just for reference. The detail specification and drawing sheets will be provided upon request. Copyright. 2013 DONGYANG Electronic Inc. All rights reserved

OUTLINE DIMENSION






Note: All unspecified tolerance according to following table.

Outline dimensions hadn't specified tolerance	
Outline Dimensions	Tolerance
≤10	±0.3
10~50	±0.6
>50	±1

WIRING DIAGRAM



Note: No polarity on the load and coil

Dimension

COIL DATA @ 23℃

Nominal Voltage (VDC)	Coil Power (W)	Nominal Current (A)	Coil Resistance (Ω±10%)	Pick-up Voltage (VDC)	Drop-out Voltage (VDC)
12	2.6	0.22	55.4	9.0 Max.	1 Min.
24	2.6	0.11	221.6	18.0 Max.	2 Min.

Coil data

TEL: 02 - 716 - 6737~8 FAX: 02 - 701 - 8424 E - mail: webmaster@dongyangele.co.kr www.dongyangele.co.kr

Specifications are subject to change without notice. Specifications in this catalog are just for reference. The detail specification and drawing sheets will be provided upon request. Copyright. 2013 DONGYANG Electronic Inc. All rights reserved

Technical Data	
Insulation Resistance	＞1000 MΩ (at 1000 VDC)
Dielectric Strength	4,000VAC 50/60Hz 1min
Temperature Range	- 40℃ ~ +85℃
Coil Power	2.6W
Contact Load	20A High Voltage
Contact Arrangement	1 Form A

TEL: 02 - 716 - 6737~8 FAX: 02 - 701 - 8424 E - mail: webmaster@dongyangele.co.kr www.dongyangele.co.kr

Specifications are subject to change without notice. Specifications in this catalog are just for reference. The detail specification and drawing sheets will be provided upon request. Copyright. 2013 DONGYANG Electronic Inc. All rights reserved