# TMC2K2J - 칩트리머 - 상품코드 : 020300133



*오픈타입 칩트리머 가변저항기
*최적의 공간활용 사이즈
*저항값 : 100Ω~ 2.2㏁
*리플로우 솔더링에 적합

## 제품 상세 정보 (Product Features)

* Space Saving Size
* Easily adjusts with standard screwdriver.
* Metal - glaze resistanceelement gives excellent stabilityand protection against environmental factors.
* Canbe mountedto a circuit board with adhesive.
* Designed for reflow soldering.
* Supplied in 8mm tape for automatic assembly equipment.
* Conform RoHS

"추가제품옵션"을 통해서 "조절방향 및 저항값 선택" 가능합니다.

※ 유의사항

상기 제품에 첨부된 데이터시트는 참고용입니다.
자세한 데이터시트를 원하실 때에는 당사에 문의 바랍니다.

## 기술데이터


| Technical Data | |
|---|---|
| Endurance cycles | 10cycles |
| Adjustment Travel | Endless(effective angle260±20) |
| Resistance Range | 100Ω~2.2MΩ |
| Resistance Tolerance | Within ±30% |
| Power Rating | 0.15 W at 70℃ |
| Maximum Rated Voltage | AC50V, DC50V |
| Temperatuer Range | -40℃~100℃ |
| Rotational Torque | 0.5 to 15mN |




TEL: 02 - 716 - 6737~8 FAX: 02 - 701 - 8424 E - mail: webmaster@dongyangele.co.kr www.dongyangele.co.kr

Specifications are subject to change without notice. Specifications in this catalog are just for reference. The detail specification and drawing sheets will be provided upon request. Copyright. 2013 DONGYANG Electronic Inc. All rights reserved

## Drawing




Dimension





REEL DIMENSION



TEL: 02 - 716 - 6737~8 FAX: 02 - 701 - 8424 E - mail: webmaster@dongyangele.co.kr www.dongyangele.co.kr

Specifications are subject to change without notice. Specifications in this catalog are just for reference. The detail specification and drawing sheets will be provided upon request. Copyright. 2013 DONGYANG Electronic Inc. All rights reserved




REFLOW SOLDERING REQUIREMENTS



TEL: 02 - 716 - 6737~8 FAX: 02 - 701 - 8424 E - mail: webmaster@dongyangele.co.kr www.dongyangele.co.kr

Specifications are subject to change without notice. Specifications in this catalog are just for reference. The detail specification and drawing sheets will be provided upon request. Copyright. 2013 DONGYANG Electronic Inc. All rights reserved