PDB183 - GTR 시리즈 - 17mm Guitar Potentiometer - 상품코드 : 020300139



- Split knurled or plain shaft options
- DPDT push - pull switch
- Metal bushing and shaft

제품 상세 정보 (Product Features)

- Carbon element
- Linear and audio taper options
- RoHS compliant*

"추가제품옵션"을 통해서 "샘플&견적요청"가능합니다.

※ 유의사항

상기 제품에 첨부된 데이터시트는 참고용입니다.
자세한 데이터시트를 원하실 때에는 당사에 문의 바랍니다.

핵심 정보 (Key information)


Linear Power Rating	0.2 watt
Audio Power Rating	0.1 watt
턴 수	Single Turn
저항	10K ohms to 1M ohms
Resistance Tolerance	+/- 20 %

기술데이터


TEL: 02 - 716 - 6737~8 FAX: 02 - 701 - 8424 E - mail: webmaster@dongyangele.co.kr www.dongyangele.co.kr

Specifications are subject to change without notice. Specifications in this catalog are just for reference. The detail specification and drawing sheets will be provided upon request. Copyright. 2013 DONGYANG Electronic Inc. All rights reserved

Drawing



Dimension1




Dimension2

TEL: 02 - 716 - 6737~8 FAX: 02 - 701 - 8424 E - mail: webmaster@dongyangele.co.kr www.dongyangele.co.kr

Specifications are subject to change without notice. Specifications in this catalog are just for reference. The detail specification and drawing sheets will be provided upon request. Copyright. 2013 DONGYANG Electronic Inc. All rights reserved

Product Dimensions


PDB183-GTR11,
PDB183-GTR13



Dimension3

Product Dimensions


PDB183-GTR21,
PDB183-GTR22



Dimension4

Product Dimensions

PDB183-GTR31,
PDB183-GTR32




Dimension5

TEL: 02 - 716 - 6737~8 FAX: 02 - 701 - 8424 E - mail: webmaster@dongyangele.co.kr www.dongyangele.co.kr

Specifications are subject to change without notice. Specifications in this catalog are just for reference. The detail specification and drawing sheets will be provided upon request. Copyright. 2013 DONGYANG Electronic Inc. All rights reserved

Audio Taper Plot



Chart

Electrical Characteristics	
Resistance Tolerance	±20 %
Resistance Value	10K ~ 1M
Insulation Resistance	
Independent Linearity	

Environmental Characteristics	
Operating Temperature	- 10 ° C to + 50 ° C
Sliding Noise	47 mV max.

Mechanical Charateristics	
Mechanical Angle	300 ° ±5 °
Rotational Torque	30 to 100 g - cm
Soldering Condition	260 ° C max. within 3 seconds

TEL: 02 - 716 - 6737~8 FAX: 02 - 701 - 8424 E - mail: webmaster@dongyangele.co.kr www.dongyangele.co.kr

Specifications are subject to change without notice. Specifications in this catalog are just for reference. The detail specification and drawing sheets will be provided upon request. Copyright. 2013 DONGYANG Electronic Inc. All rights reserved